

View Online at <https://aerobasegroup.com/nsn/5935-00-985-0371>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, flush mount

Overall Length:

Between 1.099 inches and 1.119 inches

Overall Height:

Between 3.365 inches and 3.385 inches

Overall Width:

Between 3.927 inches and 3.947 inches

Unthreaded Mounting Hole Diameter:

0.144 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.995 inches and 1.005 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 2.870 inches and 2.880 inches

Distance From Mounting Shoulder To Front Face:

Between 0.740 inches and 0.760 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

2

Contact Removability:

Nonremovable all mating ends single contact grouping

Polarization Method:

2 polarization posts

Shell Type:

Solid

Connector Locking Method:

Screw

Thready Qty Per Inch (tpi):

12

Thread Size:

0.312 inches

Terminal Location:

Back all mating ends single contact grouping

Contact Material:

Copper alloy all mating ends single contact grouping

Contact Surface Treatment:

Gold all mating ends single contact grouping or silver all mating ends single contact grouping

Insert Material:

Plastic melamine all mating ends or plastic phenolic all mating ends

Terminal Type:

Solder well all mating ends single contact grouping

Guide Design And Location:

Hexagon shape male post right-hand at 11 oclock

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.028 gold grains, troy and 0.028 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0