Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-985-0374

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, flush mount
Overall Length:
Between 1.099 inches and 1.119 inches
Overall Height:
Between 3.385 inches and 3.865 inches
Overall Width:
Between 3.927 inches and 3.947 inches
Unthreaded Mounting Hole Diameter:
0.144 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 0.995 inches and 1.005 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 2.870 inches and 2.880 inches
Distance From Mounting Shoulder To Front Face:
Between 0.740 inches and 0.760 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
2
Contact Position Arrangement Style:
14 all mating ends
Contact Removability:
Nonremovable all mating ends single contact grouping
Polarization Method:
2 polarization posts
Shell Type:
Solid
Thready Qty Per Inch (tpi):
12
Thread Size:
0.312 inches
Terminal Location:
Back all mating ends single contact grouping
Contact Material:
Copper alloy all mating ends single contact grouping
Contact Surface Treatment:
Gold all mating ends single contact grouping or silver all mating ends single contact grouping

Gold all mating ends single contact grouping or silver all mating ends single contact grouping



Insert Material:

Plastic melamine all mating ends or plastic phenolic all mating ends

Terminal Type:

Solder well all mating ends single contact grouping

Guide Design And Location:

Hexagon shape male post right-hand at 7 oclock

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.028 gold grains, troy and 0.028 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0