Electrical Receptacle Connector - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5935-00-985-2719

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
1.141 inches
Overall Height:
1.281 inches
Overall Width:
1.281 inches
Unthreaded Mounting Hole Diameter:
Between 0.118 inches and 0.124 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 0.964 inches and 0.974 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.964 inches and 0.974 inches
Distance From Mounting Shoulder To Front Face:
Between 0.562 inches and 0.572 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
Contact Position Arrangement Style:
16s-1 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
13.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell



Thread Length: 0.450 inches Thready Qty Per Inch (tpi): 20 **Thread Size:** 1.000 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Rubber single mating end **Terminal Type:** Crimp single mating end single contact grouping Shell Material: Aluminum alloy **Shell Surface Treatment:** Cadmium and chromate **Included Contact Quantity:** 7 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.007 gold grains, troy and 0.007 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A039b0