## NSN 5935-00-986-7414

Plug-in Electronic Components Socket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-986-7414 **Body Material:** Plastic **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Top mount w/studs **Fabrication Method:** Molded **Overall Length:** 1.250 inches **Overall Height:** 0.610 inches **Overall Width:** 0.318 inches **Mounting Hole Diameter:** 0.112 inches **Mounting Hole Style:** Two mounting holes/slots, diagonal **Specific Equipment Accommodated:** Relay **Contact Maximum Current Rating In Amps:** 3.0 **Contact Material:** Phosphor bronze **Contact Surface Treatment:** Gold and silver **Accommodated Contact Quantity:** Center To Center Distance Between Outside Mounting Holes Along Length: 1.000 inches **Center To Center Distance Between Outside Mounting Holes Along Width:** 0.125 inches **Polarization Type:** Contact position **Projection Length Below Mounting Surface:** 0.189 inches **Mounting Method:** Threaded stud

Chassis

**Mounting Type For Which Designed:** 

## NSN 5935-00-986-7414

Plug-in Electronic Components Socket - Page 2 of 2



| Thready Qty Per Inch (tpi):  |
|--|
| 40   |
| Thread Size:   |
| 0.112 inches   |
| Contact Position Arrangement Style:  |
| Symmetrical  |
| Precious Material And Location:  |
| Contact surfaces gold and contact surfaces silver  |
| Precious Material And Weight:  |
| $0.008 \ \text{gold grains}, \ \text{troy} \ \text{and} \ 0.008 \ \text{silver grains}, \ \text{troy}$ |
| Precious Material:   |
| Gold and silver  |
| Thread Series Designator:  |
| Unc  |
| Terminal Type And Quantity:  |
| 8 solder well  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A02300   |