

View Online at <https://aerobasegroup.com/nsn/5935-00-987-5911>

Body Style:

Straight shape

Overall Length:

1.130 inches

Overall Height:

2.490 inches

Overall Width:

0.950 inches

Mating End Quantity:

3

Contact Position Arrangement Style:

Nonstd 3rd mating end

Contact Removability:

Nonremovable all mating ends single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 all mating ends single contact grouping

Shell Type:

Solid

Connector Locking Method:

Bayonet slot and spring friction

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 1st mating end single contact grouping

Operating Temperature Rating:

50.0 degrees celsius

Contact Material:

Copper alloy all mating ends single contact grouping

Contact Surface Treatment:

Nickel 3rd mating end single contact grouping

Insert Material:

Plastic polytetrafluoroethylene 1st mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response 1st mating end single contact grouping

Shell Material:

Copper alloy

Included Contact Quantity:

1 2nd mating end single contact grouping

Included Contact Type:

Coaxial pin 1st mating end single contact grouping

Special Features:

Plastic, phenolic

Precious Material And Location:

Contact surface gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.