

View Online at <https://aerobasegroup.com/nsn/5935-00-987-8735>

Body Style:

Straight shape w/flange

Overall Length:

Between 1.045 inches and 1.056 inches

Overall Height:

Between 0.796 inches and 0.828 inches

Overall Width:

Between 0.796 inches and 0.828 inches

Environmental Protection:

Pressure proof

Unthreaded Mounting Hole Diameter:

Between 0.115 inches and 0.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.594 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.594 inches

Distance From Mounting Shoulder To Front Face:

Between 0.562 inches and 0.572 inches

Mating End Quantity:

2

Contact Position Arrangement Style:

40392 all mating ends

Contact Removability:

Nonremovable all mating ends all contact groupings

Contact Maximum Current Rating In Amps:

7.5 all mating ends all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

500.0 all mating ends all contact groupings

Contact Maximum Dc Voltage Rating In Volts:

700.0 all mating ends all contact groupings

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Contact Material:

Copper alloy all mating ends all contact groupings

Contact Surface Treatment:

Gold all mating ends all contact groupings and silver all mating ends all contact groupings

Insert Material:

Rubber all mating ends

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate

Included Contact Quantity:

2 all mating ends single contact grouping

Included Contact Type:

Round socket 2nd mating end all contact groupings

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.002 gold grains, troy and 0.002 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0