## NSN 5935-00-988-3550

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-988-3550

**Body Style:** Right angle type **Overall Length:** 3.257 inches **Overall Width:** 0.352 inches **Body Height:** 0.461 inches **Environmental Protection:** Moisture resistant and salt water resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.128 inches **Distance Between Mounting Facility Centers:** 2.937 inches **Mating End Quantity: Contact Position Arrangement Style:** 1 row of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 600.0 single mating end single contact grouping **Terminal Location:** Side single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and copper single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Criticality Code Justification:** Feat **Terminal Type:** Tab, solder lug single mating end single contact grouping **Insert Material Specification:** Mil-m-14, type mdg military specification single material response single mating end

## Included Contact Quantity:

13 single mating end single contact grouping

## **Included Contact Type:**

Flat pin single mating end single contact grouping

## NSN 5935-00-988-3550

Electrical Receptacle Connector - Page 2 of 2



Special Features:
Contact no. 2 and no. 3 removed
<b>Precious Material And Location</b>
Contact surfaces gold
<b>Precious Material And Weight:</b>
0.013 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-m-14 spec.