

View Online at <https://aerobasegroup.com/nsn/5935-00-988-6014>

Body Style:

Straight edge type w/mounting flange

Overall Length:

4.500 inches

Overall Height:

0.720 inches

Overall Width:

0.440 inches

Environmental Protection:

Salt water resistant

Unthreaded Mounting Hole Diameter:

0.140 inches

Distance Between Mounting Facility Centers:

4.250 inches

Board Accommodated Length:

3.875 inches single board

Board Accommodated Width:

Between 0.054 inches and 0.071 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

Bridged contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Fixed contact to contact

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, class 1 military specification 1st treatment response single mating end single contact grouping

Terminal Type:

Tab, solder lug single mating end single contact grouping

Contact Material Specification:

Qq-b-750 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-19833, ty gdi-30 military specification single material response single mating end

Included Contact Quantity:

31 single mating end single contact grouping

Included Contact Type:

Bifurcated spring single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.031 gold grains, troy and 0.031 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.