

View Online at <https://aerobasegroup.com/nsn/5935-00-988-6301>

**Environmental Protection:**

Heat resistant and moisture resistant and oil tight and pressure proof and salt water resistant and vibration resistant

**Mating End Quantity:**

1

**Contact Removability:**

Removable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:**

7.5 single mating end 2nd contact grouping

**Polarization Method:**

Key, multiple key groove

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet pin

**Connector Cable Strain Relief Method:**

Cable clamp

**Terminal Location:**

Back single mating end all contact groupings

**Contact Surface Treatment:**

Silver single mating end all contact groupings and rhodium single mating end all contact groupings

**Insert Material:**

Rubber silicone class q single mating end

**Terminal Type:**

Crimp single mating end all contact groupings

**Shell Material:**

Aluminum alloy

**Included Contact Quantity:**

6 single mating end 1st contact grouping

**Included Contact Type:**

Round socket single mating end all contact groupings

**Precious Material And Location:**

Contact surfaces silver and contact surfaces rhodium

**Precious Material And Weight:**

0.032 silver grains, troy and 0.032 rhodium grains, troy

**Precious Material:**

Silver and rhodium

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0