## NSN 5935-00-988-6916

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-988-6916

**Thread Class:** 2a and 2b **Thread Direction:** Right-hand and right-hand **Overall Length:** Between 1.802 inches and 1.822 inches **Overall Height:** 0.859 inches **Overall Width:** Between 0.490 inches and 0.510 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 42 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Jackscrew **Connector Locking Method:** Jackscrew-socket **Thread Size:** 0.099 inches and 0.099 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Solder well single mating end single contact grouping **Insert Material Specification:** Mil-m-19833, type gdi-30f military specification single material response single mating end

Included Contact Quantity:

42 single mating end single contact grouping

**Included Contact Type:** 

Round socket single mating end single contact grouping

## NSN 5935-00-988-6916

Electrical Plug Connector - Page 2 of 2



Precious	Material	And	Location:
----------	----------	-----	-----------

Contact surfaces gold and contact surfaces silver

**Precious Material And Weight:** 

0.042 gold grains, troy and 0.042 silver grains, troy

**Precious Material:** 

Gold and silver

**Thread Series Designator:** 

Unc and unc

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-19833 spec.