## NSN 5935-00-988-9079

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-988-9079

**Thread Class:** 

2b and 2a

**Thread Direction:** 

Right-hand and right-hand

**Body Style:** 

Straight shape

**Overall Length:** 

Between 2.565 inches and 2.595 inches

**Overall Height:** 

Between 0.760 inches and 0.780 inches

**Overall Width:** 

Between 0.490 inches and 0.510 inches

**Distance Between Mounting Facility Centers:** 

Between 2.199 inches and 2.215 inches

**Threaded Device Type:** 

Coupling facility and mounting stud

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

15 single mating end

**Contact Removability:** 

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

10.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:** 

1000.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:** 

1400.0 single mating end single contact grouping

**Polarization Method:** 

Contact

**Connector Locking Method:** 

Screw lock pin

Thready Qty Per Inch (tpi):

32 and 40

**Thread Size:** 

0.138 inches and 0.112 inches

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and silver single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate single mating end

# NSN 5935-00-988-9079

Electrical Receptacle Connector - Page 2 of 2



#### **Contact Surface Treatment Specification:**

Qq-s-365, type 1, grade b federal specification 2nd treatment response single mating end single contact grouping

### **Terminal Type:**

Solder well single mating end single contact grouping

### **Insert Material Specification:**

Mil-m-14, type sdi-5 military specification single material response single mating end

### **Included Contact Quantity:**

15 single mating end single contact grouping

### **Included Contact Type:**

Round pin single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

#### **Precious Material And Weight:**

0.015 gold grains, troy and 0.015 silver grains, troy

#### **Precious Material:**

Gold and silver

### **Thread Series Designator:**

Unc and unc

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A039b0

### Mil-std (military Standard):

Mil-m-14 spec.