

View Online at <https://aerobasegroup.com/nsn/5935-00-989-1619>

Thread Class:

2a and 2a and 2b

Thread Direction:

Right-hand and right-hand and right-hand

Body Style:

Straight shape, external coupling, w/clamp

Overall Length:

2.125 inches

Overall Diameter:

2.040 inches

Environmental Protection:

Pressure proof and heat resistant and moisture resistant and oil tight and salt water resistant and vibration resistant

Cable Entrance Diameter:

0.940 inches

Distance From Mounting Shoulder To Front Face:

0.781 inches

Mounting Facility Thickness:

Between 0.062 inches and 0.125 inches

Threaded Device Type:

Coupling facility and mounting bushing

Mating End Quantity:

15

Contact Position Arrangement Style:

16-55 single mating end

Polarization Method:

Keyway or multiple keyway and jackscrew

Insert Position In Deg:

0.0 and 90.0 and 270.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Connector Cable Strain Relief Method:

Cable clamp and cord protector

Thready Qty Per Inch (tpi):

18 and 20

Thread Size:

1.438 inches and 1.500 inches and 1.500 inches

Insert Material:

Rubber single mating end

Shell Material:

Aluminum alloy and cadmium

Shell Surface Treatment:

Cadmium and iridium

Bushing Accommodation Hole Shape:

Round w/flat

Thread Series Designator:

Unef and un

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0