

View Online at <https://aerobasegroup.com/nsn/5935-00-989-1619>

**Thread Class:**

2a and 2a and 2b

**Thread Direction:**

Right-hand and right-hand and right-hand

**Body Style:**

Straight shape, external coupling, w/clamp

**Overall Length:**

2.125 inches

**Overall Diameter:**

2.040 inches

**Environmental Protection:**

Pressure proof and heat resistant and moisture resistant and oil tight and salt water resistant and vibration resistant

**Cable Entrance Diameter:**

0.940 inches

**Distance From Mounting Shoulder To Front Face:**

0.781 inches

**Mounting Facility Thickness:**

Between 0.062 inches and 0.125 inches

**Threaded Device Type:**

Coupling facility and mounting bushing

**Mating End Quantity:**

15

**Contact Position Arrangement Style:**

16-55 single mating end

**Polarization Method:**

Keyway or multiple keyway and jackscrew

**Insert Position In Deg:**

0.0 and 90.0 and 270.0

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Connector Cable Strain Relief Method:**

Cable clamp and cord protector

**Thready Qty Per Inch (tpi):**

18 and 20

**Thread Size:**

1.438 inches and 1.500 inches and 1.500 inches

**Insert Material:**

Rubber single mating end

**Shell Material:**

Aluminum alloy and cadmium

**Shell Surface Treatment:**

Cadmium and iridium

**Bushing Accommodation Hole Shape:**

Round w/flat

**Thread Series Designator:**

Unef and un

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0