## NSN 5935-00-989-5644

Telephone Jack - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-989-5644 **Thread Class:** 2a **Thread Direction:** Right-hand **Electrical Insulation Feature:** Uninsulated **Body Style:** Threaded bushing mounted **Overall Length:** 1.280 inches **Mounting Bushing Length:** Between 0.260 inches and 0.300 inches **Overall Diameter:** Between 0.730 inches and 0.770 inches **Bushing Accommodation Hole Shape:** Round **Maximum Voltage Rating In Volts:** 500.0 ac **Accommodated Finger Type:** Three conductor, cone tip single finger **Finger Accommodation Diameter:** 0.251 inches single finger and 0.253 inches single finger **Finger Accommodation Length:** 1.250 inches single finger **Bushing Thru-hole Accommodation Diameter:** 0.375 inches **Jack Contact Arrangement Designator:** J10 **Mounting Facility Type And Quantity:** 1 bushing Thready Qty Per Inch (tpi): **Thread Size:** 0.375 inches **Terminal Type:** Tab, solder lug Material: Plastic, phenolic insulator Material: Plastic phenolic insulator

Surface Treatment: Tin terminal

## NSN 5935-00-989-5644

Telephone Jack - Page 2 of 2



	S	ur	fa	се	Tr	e	at	m	er	١t	
--	---	----	----	----	----	---	----	---	----	----	--

Nickel bushing

**Thread Series Designator:** 

Unef

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03400