NSN 5935-00-989-6006

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-989-6006

Thread Direction: Right-hand **Body Style:** Straight edge type w/mounting flange **Overall Length:** 4.340 inches **Overall Height:** 0.440 inches **Overall Width:** 0.326 inches **Environmental Protection:** Vibration resistant **Unthreaded Mounting Hole Diameter:** 0.133 inches **Distance Between Mounting Facility Centers:** 4.036 inches **Board Accommodated Length:** 3.720 inches single board **Mating End Quantity: Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Contact to contact polarizing keys **Terminal Location:** Front single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic single mating end **Terminal Type:** Solder well single mating end single contact grouping **Included Contact Quantity:** 22 single mating end single contact grouping **Included Contact Type:** Spring pincers single mating end single contact grouping **Special Features:** Polarization position r **Precious Material And Location:**

Contact surface gold

NSN 5935-00-989-6006

Electrical Receptacle Connector - Page 2 of 2



Precious	Material:
----------	-----------

Gold

Test Data Document:

81312-milc21097 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0