

View Online at https://aerobasegroup.com/nsn/5935-00-989-6866

## Body Style:

Straight shape

## Overall Length:

Between 2.073 inches and 2.103 inches

#### **Overall Height:**

Between 0.416 inches and 0.436 inches

#### **Overall Width:**

Between 0.479 inches and 0.509 inches

#### **Environmental Protection:**

Moisture resistant and vibration resistant

#### **Unthreaded Mounting Hole Diameter:**

Between 0.115 inches and 0.125 inches

#### **Distance Between Mounting Facility Centers:**

Between 1.847 inches and 1.857 inches

#### Mating End Quantity:

1 Contact Position Arrangement Style:

13w3 single mating end

## Contact Removability:

Removable single mating end single contact grouping

#### **Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

#### **Polarization Method:**

Mating end

#### Shell Type:

Solid

#### **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper single mating end single contact grouping

## **Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

## **Insert Material:**

Plastic diallyl phthalate single mating end

## **Terminal Type:**

Crimp single mating end single contact grouping

## Shell Material:

Steel

## Shell Surface Treatment:

Cadmium and chromate

## Insert Material Specification:

Mil-m-19833, type gdi-30f military specification single material response single mating end

# NSN 5935-00-989-6866

Electrical Receptacle Connector - Page 2 of 2



**Included Contact Quantity:** 10 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.010 gold grains, troy and 0.010 silver grains, troy **Precious Material:** Gold and silver Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-m-19833 spec.