NSN 5935-00-989-7066

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-989-7066 **Overall Length:** 2.312 inches **Overall Height:** 1.166 inches Overall Width: 1.125 inches **Environmental Protection:** Moisture resistant **Unthreaded Mounting Hole Diameter:** 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.750 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 2.062 inches **Mating End Quantity: Contact Position Arrangement Style:** 16 single mating end **Contact Removability:** Nonremovable single mating end all contact groupings **Contact Maximum Current Rating In Amps:** 7.5 single mating end 3rd contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 900.0 single mating end 2nd contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end 3rd contact grouping **Polarization Method:** Mating end Shell Type: Solid **Terminal Location:** Back single mating end all contact groupings **Contact Material:** Copper alloy single mating end all contact groupings **Contact Surface Treatment:** Gold single mating end all contact groupings and silver single mating end all contact groupings **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Solder well single mating end all contact groupings **Shell Material:**

Aluminum alloy

NSN 5935-00-989-7066

Mil-std (military Standard):

Mil-m-14 spec.

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Cadmium
Insert Material Specification:
Mil-m-14, type mdg military specification single material response single mating end
Included Contact Quantity:
9 single mating end 3rd contact grouping
Included Contact Type:
Round pin single mating end 3rd contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.016 gold grains, troy and 0.016 silver grains, troy
Precious Material:
Gold and silver
Test Data Document:
81349-c-21617 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-c-21617 government specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A039b0