## NSN 5935-00-990-4464

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-990-4464 **Thread Class:** 2a **Thread Direction:** Right-hand **Overall Length:** 1.718 inches **Bushing Diameter:** 1.875 inches **Overall Diameter:** 2.062 inches **Environmental Protection:** Pressure proof **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** 28-21 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 22.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 0.0 Shell Type: **Connector Locking Method:** Spring friction Thready Qty Per Inch (tpi):

18 Thread Size: 1.875 inches

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and silver single mating end single contact grouping

## NSN 5935-00-990-4464

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Steel comp 304
Shell Surface Treatment:
Passivate
Shell Material Specification:
Qq-s-763, class 304 federal specification single material response
Included Contact Quantity:
37 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Round socket single mating end single contact grouping
Test Data Document:
81349-mil-c-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Uns
Specification Or Standard:
E class
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0