

View Online at https://aerobasegroup.com/nsn/5935-00-990-7373

Body Material:
Any acceptable
Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Top mount w/metal saddle and bushings
Overall Length:
1.969 inches
Overall Height:
1.062 inches
Overall Width:
1.281 inches
Body Mounting Hole Accommodation Diameter:
1.118 inches
Distance Between Mounting Facility Centers:
1.562 inches
Mounting Hole Style:
Round, w/two mounting holes
Contact Maximum Current Rating In Amps:
10.0
10.0 Contact Material:
Contact Material:
Contact Material: Phosphor bronze
Contact Material: Phosphor bronze Contact Surface Treatment:
Contact Material: Phosphor bronze Contact Surface Treatment: Gold and silver
Contact Material: Phosphor bronze Contact Surface Treatment: Gold and silver Accommodated Contact Quantity:
Contact Material: Phosphor bronze Contact Surface Treatment: Gold and silver Accommodated Contact Quantity: 14
Contact Material: Phosphor bronze Contact Surface Treatment: Gold and silver Accommodated Contact Quantity: 14 Polarization Type:
Contact Material: Phosphor bronze Contact Surface Treatment: Gold and silver Accommodated Contact Quantity: 14 Polarization Type: Contact position
Contact Material: Phosphor bronze Contact Surface Treatment: Gold and silver Accommodated Contact Quantity: 14 Polarization Type: Contact position Projection Length Above Mounting Surface:
Contact Material: Phosphor bronze Contact Surface Treatment: Gold and silver Accommodated Contact Quantity: 14 Polarization Type: Contact position Projection Length Above Mounting Surface: 0.500 inches
Contact Material: Phosphor bronze Contact Surface Treatment: Gold and silver Accommodated Contact Quantity: 14 Polarization Type: Contact position Projection Length Above Mounting Surface: 0.500 inches Mounting Method:
Contact Material: Phosphor bronze Contact Surface Treatment: Gold and silver Accommodated Contact Quantity: 14 Polarization Type: Contact position Projection Length Above Mounting Surface: 0.500 inches Mounting Method: Threaded stud
Contact Material: Phosphor bronze Contact Surface Treatment: Gold and silver Accommodated Contact Quantity: 14 Polarization Type: Contact position Projection Length Above Mounting Surface: 0.500 inches Mounting Method: Threaded stud Mounting Type For Which Designed:
Contact Material: Phosphor bronze Contact Surface Treatment: Gold and silver Accommodated Contact Quantity: 14 Polarization Type: Contact position Projection Length Above Mounting Surface: 0.500 inches Mounting Method: Threaded stud Mounting Type For Which Designed: Chassis
Contact Material: Phosphor bronze Contact Surface Treatment: Gold and silver Accommodated Contact Quantity: 14 Polarization Type: Contact position Projection Length Above Mounting Surface: 0.500 inches Mounting Method: Threaded stud Mounting Type For Which Designed: Chassis Thready Qty Per Inch (tpi):
Contact Material: Phosphor bronze Contact Surface Treatment: Gold and silver Accommodated Contact Quantity: 14 Polarization Type: Contact position Projection Length Above Mounting Surface: 0.500 inches Mounting Method: Threaded stud Mounting Type For Which Designed: Chassis Thready Qty Per Inch (tpi): 32

Concentric



**Precious Material And Location:** 

Contact surfaces gold and contact surfaces silver

### **Precious Material And Weight:**

0.014 gold grains, troy and 0.014 silver grains, troy

#### **Precious Material:**

Gold and silver

# **Thread Series Designator:**

Unc

### Terminal Type And Quantity:

14 solder well

Shelf Life:

N/a

## Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A02300