Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-990-7444
Body Style:
Straight shape
Overall Length:
2.094 inches
Overall Height:
0.429 inches
Overall Width:
0.494 inches
Environmental Protection:
Shock proof and vibration resistant
Unthreaded Mounting Hole Diameter:
0.120 inches
Distance Between Mounting Facility Centers:
1.852 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
9w4 single mating end
Contact Removability:
Nonremovable single mating end all contact groupings
Contact Maximum Current Rating In Amps:
7.5 single mating end all contact groupings
Polarization Method:
Mating end
Shell Type:
Solid
Terminal Location:
Back single mating end all contact groupings
Contact Material:
Copper alloy single mating end all contact groupings
Contact Surface Treatment:
Gold single mating end all contact groupings and silver single mating end all contact groupings
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Solder well single mating end all contact groupings
Shell Material:
Steel
Shell Surface Treatment:
Cadmium and chromate
Shell Material Specification:
On a COO fordered encodification single metarial responses

Qq-s-698 federal specification single material response

NSN 5935-00-990-7444

Electrical Receptacle Connector - Page 2 of 2



Insert Material Specification:

Mil-m-19833, typegdi-30f military specification single material response single mating end

Included Contact Quantity:

5 single mating end 2nd contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.009 gold grains, troy and 0.009 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-19833 spec.