Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-992-1782

Thread Class:
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Height:
1.344 inches
Overall Width:
1.344 inches
Unthreaded Mounting Hole Diameter:
0.150 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.031 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.031 inches
Distance From Mounting Shoulder To Front Face:
0.462 inches
Threaded Device Type:
Back shell
Mating End Quantity:
1
Contact Position Arrangement Style:
14s-2 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
13.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
200.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
250.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Thready Qty Per Inch (tpi):
20

## NSN 5935-00-992-1782

Electrical Receptacle Connector - Page 2 of 2



	ead Size:
	12 inches
	minal Location:
	k single mating end single contact grouping
	ntact Material:
	oper alloy single mating end single contact grouping
Cor	ntact Surface Treatment:
Silv	er single mating end single contact grouping
Inse	ert Material:
Rub	ober single mating end
Ter	minal Type:
	np single mating end single contact grouping
	ell Material:
	minum
She	ell Surface Treatment:
Cad	dmium and chromate
Incl	luded Contact Quantity:
4 si	ngle mating end single contact grouping
Incl	luded Contact Type:
Rou	and pin single mating end single contact grouping
Pre	cious Material And Location:
Cor	ntact surfaces silver
Pre	cious Material And Weight:
0.00	04 silver grains, troy
Pre	cious Material:
Silv	er
Thr	ead Series Designator:
Une	əf
She	elf Life:
N/a	
Uni	t Of Measure:
Der	nilitarization:
No	
Fiig	<b>j:</b>
A03	3960