Electrical Receptacle Connector - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5935-00-992-2210

Thread Class:	
2a	
Thread Direction:	
Right-hand	
Body Style:	
Straight shape, external coupling	
Overall Length:	
1.391 inches	
Overall Height:	
1.625 inches	
Overall Width:	
1.625 inches	
Unthreaded Mounting Hole Diameter:	
Between 0.118 inches and 0.124 inches	
Center To Center Distance Between Mounting Facilities Parallel To Height:	
Between 1.245 inches and 1.255 inches	
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:	
Between 1.245 inches and 1.255 inches	
Distance From Mounting Shoulder To Front Face: Between 0.750 inches and 0.760 inches	
Threaded Device Type:	
Coupling facility	
Mating End Quantity:	
1 Oranizat Danifican Amerikan Afrika	
Contact Position Arrangement Style:	
22-20 single mating end	
Contact Removability:	
Removable single mating end single contact grouping	
Contact Maximum Current Rating In Amps:	
13.0 single mating end single contact grouping	
Contact Maximum Ac Voltage Rating In Volts:	
500.0 single mating end single contact grouping	
Contact Maximum Dc Voltage Rating In Volts:	
700.0 single mating end single contact grouping	
Polarization Method:	
Keyway or multiple keyway	
Insert Position In Deg:	
110.0	
Shell Type:	
Solid	
Connector Locking Method:	
Externally threaded shell	



Thread Length: 0.625 inches **Thread Size:** 1.375 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Rubber single mating end **Terminal Type:** Crimp single mating end single contact grouping Shell Material: Aluminum alloy **Included Contact Quantity:** 9 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.009 gold grains, troy and 0.009 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0