NSN 5935-00-992-4724

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-992-4724

| Body Style: |
|---|
| Straight shape, flush mount |
| Overall Length: |
| 1.250 inches |
| Overall Height: |
| 1.064 inches |
| Overall Width: |
| 1.064 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.188 inches |
| Mating End Quantity: |
| 1 |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Polarization Method: |
| Mating end |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Friction |
| Connector Cable Strain Relief Method: |
| Bracket |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| Insert Material: |
| Plastic diallyl phthalate single mating end |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Shell Material: |
| Metal |
| Shell Surface Treatment: |
| Chromium |
| Insert Material Specification: |
| Mil-m-19833m type gdi-30f military specification single material response single mating end |
| Unable To Decode: |
| Unable to decode and unable to decode |

Included Contact Quantity:

7 single mating end single contact grouping

NSN 5935-00-992-4724

Electrical Receptacle Connector - Page 2 of 2



| Included Contact Type: |
|---|
| Round pin single mating end single contact grouping |
| Special Features: |
| 2 polarizing pins |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.007 gold grains, troy |
| Precious Material: |
| Gold |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |

Mil-std (military Standard):

Mil-m-19833m spec.