NSN 5935-00-992-6624

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-992-6624
Body Style:
Straight shape threaded
Overall Length:
0.765 inches
Overall Diameter:
0.750 inches
Environmental Protection:
Moisture resistant and vibration resistant and salt water resistant
Mounting Facility Thickness:
0.062 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
3p single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Ball
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Rubber chloroprene class cr single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium

Included Contact Quantity:

3 single mating end single contact grouping

NSN 5935-00-992-6624

Electrical Receptacle Connector - Page 2 of 2



I	Incl	hul	ed	Co	ntac	:t]	Γνη	۵.
ı		ıuu	cu	-	ıııav	<i>-</i> L	V	₹.

Round pin single mating end single contact grouping

Special Features:

Solder flange mounted

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.003 gold grains, troy and 0.003 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0