

View Online at <https://aerobasegroup.com/nsn/5935-00-992-6626>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape threaded

Overall Length:

0.765 inches

Overall Diameter:

0.750 inches

Mounting Facility Thickness:

0.062 inches

Threaded Device Type:

Mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

3p single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Detent

Thready Qty Per Inch (tpi):

24

Thread Size:

0.562 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Insert Material:

Rubber chloroprene class cr single mating end

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Included Contact Quantity:

3 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.003 gold grains, troy and 0.003 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0