Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-993-0232

| Thread Class: |
|--|
| 2a |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight shape |
| Overall Length: |
| 2.900 inches |
| Overall Height: |
| 0.703 inches |
| Overall Width: |
| 0.360 inches |
| Distance Between Mounting Facility Centers: |
| 2.600 inches |
| Threaded Device Type: |
| Mounting stud |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 15 single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 7.5 single mating end single contact grouping |
| Polarization Method: |
| Guide pin/socket |
| Thread Length: |
| 0.250 inches |
| Thready Qty Per Inch (tpi): |
| 40 |
| Thread Size: |
| 0.112 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| Insert Material: |
| Plastic melamine single mating end |
| Terminal Type: |
| Colden well aimple meeting and aimple contect growning |

Solder well single mating end single contact grouping

NSN 5935-00-993-0232

Electrical Receptacle Connector - Page 2 of 2



Insert Material Specification:

Mil-m-14, type mme military specification single material response single mating end

Included Contact Quantity:

15 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization: No Fiig: A039b0 Mil-std (military Standard):

Mil-m-14 spec.