Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-993-4800

Thread	Class:
2b	
Thread I	Direction:
Right-ha	nd
Body St	yle:
Straight	shape, external coupling
Overall	Length:
1.156 ind	ches
Overall	Height:
Between	1.672 inches and 1.702 inches
Overall	Width:
Between	1.672 inches and 1.702 inches
Unthrea	ded Mounting Hole Diameter:
Between	0.164 inches and 0.174 inches
Center 1	Fo Center Distance Between Mounting Facilities Parallel To Height:
Between	1.277 inches and 1.287 inches
Distance	e Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between	1.277 inches and 1.287 inches
Distance	e From Mounting Shoulder To Front Face:
Between	0.422 inches and 0.454 inches
Threade	d Device Type:
Coupling	1 facility
Mating E	End Quantity:
1	
Contact	Position Arrangement Style:
Sk-s2 sir	ngle mating end
Contact	Removability:
Nonremo	ovable single mating end single contact grouping
Contact	Maximum Current Rating In Amps:
80.0 sing	gle mating end single contact grouping
Polariza	tion Method:
Key, mu	Itiple key groove
Insert P	osition In Deg:
0.0	
Shell Ty	pe:
Solid	
Connect	tor Locking Method:
Internally	y threaded shell
Thready	Qty Per Inch (tpi):
6	
Thread S	Size:
1.375 ind	ches

## NSN 5935-00-993-4800

Electrical Receptacle Connector - Page 2 of 2



Back sinale	e mating end single contact grouping
Contact M	
Copper allo	by single mating end single contact grouping
Contact Si	urface Treatment:
Gold single	mating end single contact grouping or silver single mating end single contact grouping
Insert Mate	erial:
Plastic mel	amine single mating end or plastic phenolic single mating end
Terminal T	уре:
Solder well	single mating end single contact grouping
Shell Mate	rial:
Aluminum	alloy
Shell Surfa	ace Treatment:
Cadmium	
Included C	Contact Quantity:
2 single ma	ating end single contact grouping
Included C	Contact Type:
Round soc	ket single mating end single contact grouping
Precious N	Naterial And Location:
Contact su	rfaces gold or contact surfaces silver
Precious N	laterial And Weight:
0.010 gold	grains, troy or 0.010 silver grains, troy
Precious N	Naterial:
Gold or silv	rer
Thread Se	ries Designator:
Unc	
Shelf Life:	
N/a	
Unit Of Me	asure:
Demilitariz	ration:
No	
Fiig:	