

View Online at <https://aerobasegroup.com/nsn/5935-00-993-8337>

Thread Class:

2a and 2b

Thread Direction:

Right-hand and right-hand

Body Style:

Hood, top opening w/clamp

Overall Length:

2.451 inches

Overall Height:

0.625 inches

Overall Width:

1.625 inches

Environmental Protection:

Moisture resistant

Cable Entrance Diameter:

0.593 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

26 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

750.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Connector Locking Method:

Jackscrew-socket

Connector Cable Strain Relief Method:

Cable clamp

Thread Size:

0.112 inches and 0.112 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Anodize

Included Contact Quantity:

26 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.026 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc and unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0