

View Online at <https://aerobasegroup.com/nsn/5935-00-993-8949>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, external coupling

**Overall Length:**

1.938 inches

**Overall Height:**

1.500 inches

**Overall Width:**

1.500 inches

**Environmental Protection:**

Moisture resistant and vibration resistant and salt water resistant

**Unthreaded Mounting Hole Diameter:**

0.120 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

1.156 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.156 inches

**Distance From Mounting Shoulder To Front Face:**

Between 0.750 inches and 0.781 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

20-7 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

22.0 single mating end all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:**

900.0 single mating end 2nd contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

700.0 single mating end 1st contact grouping

**Polarization Method:**

Key, multiple key groove

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Thread Length:**

0.625 inches

**Thread Size:**

1.250 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

**Insert Material:**

Rubber single mating end

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Surface Treatment:**

Cadmium

**Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Included Contact Quantity:**

4 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

**Precious Material:**

Gold and silver

**Test Data Document:**

81349-mil-c-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0