## NSN 5935-00-994-2566

View Online at https://aerobasegroup.com/nsn/5935-00-994-2566

Connector Adapter - Page 1 of 2



**Body Style:** Straight shape w/flange **Overall Length:** 1.125 inches **Overall Height:** 1.141 inches **Overall Width:** 1.141 inches **Environmental Protection:** Moisture resistant and salt water resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** Between 0.115 inches and 0.125 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.906 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.906 inches **Distance From Mounting Shoulder To Front Face:** Between 0.562 inches and 0.593 inches **Mating End Quantity: Contact Position Arrangement Style:** 14-5 all mating ends **Contact Removability:** Nonremovable all mating ends all contact groupings **Contact Maximum Ac Voltage Rating In Volts:** 1000.0 all mating ends all contact groupings **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 40.0 Shell Type: **Connector Locking Method:** Bayonet pin **Contact Surface Treatment:** Gold all mating ends all contact groupings and copper all mating ends all contact groupings **Shell Material:** 

Shell Surface Treatment:
Cadmium

Aluminum alloy

**Shell Surface Treatment Specification:** 

Qq-p-416, type 2, cl 3 federal specification single treatment response

## NSN 5935-00-994-2566

Connector Adapter - Page 2 of 2

Fiig: A039b0



Included Contact Quantity:
5 all mating ends single contact grouping
Included Contact Type:
Round socket 2nd mating end all contact groupings
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.025 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-c-26482 government specification
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No