# NSN 5935-00-994-6100

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-994-6100

# **Body Style:**

Straight shape, internal coupling

# **Overall Length:**

0.750 inches

# **Overall Diameter:**

0.500 inches

# **Environmental Protection:**

Moisture resistant and vibration resistant and salt water resistant

### Mating End Quantity:

1

### **Contact Position Arrangement Style:**

Bnc single mating end

# Contact Removability:

Removable single mating end single contact grouping

# Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

### Contact Maximum Frequency Rating:

4000.0 megahertz single mating end single contact grouping

# Shell Type:

Solid

# Connector Locking Method:

Bayonet latch

# **Connector Cable Strain Relief Method:**

Compression nut

### Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

### **Terminal Location:**

Back single mating end single contact grouping

### **Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

### **Insert Material:**

Plastic single mating end

### **Terminal Type:**

Solder well single mating end single contact grouping

### Shell Material:

Copper alloy

# Shell Surface Treatment:

Gold and silver

### **Shell Material Specification:**

Qq-b-626 federal specification single material response

# Included Contact Quantity:

1 single mating end single contact grouping

# NSN 5935-00-994-6100

Electrical Plug Connector - Page 2 of 2



Included Contact Type: Coaxial pin single mating end single contact grouping **Precious Material And Location:** Contact and body surfaces gold and contact and body surfaces silver **Precious Material And Weight:** 0.105 gold grains, troy and 0.105 silver grains, troy **Precious Material:** Gold and silver Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0