NSN 5935-00-994-7750

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-994-7750 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.969 inches **Overall Height:** 1.000 inches **Overall Width:** 1.000 inches **Unthreaded Mounting Hole Diameter:** 0.125 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.718 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.718 inches **Distance From Mounting Shoulder To Front Face:** 0.718 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** N single mating end **Contact Removability:** Nonremovable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Externally threaded shell Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.625 inches **Terminal Location:** Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

NSN 5935-00-994-7750

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment: Gold single mating end single contact grouping **Insert Material:** Plastic single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Copper alloy **Included Contact Quantity:** 1 single mating end single contact grouping **Included Contact Type:** Coaxial pin single mating end single contact grouping **Precious Material And Location:** Contact surface gold **Precious Material And Weight:** 0.005 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unef Shelf Life: N/a **Unit Of Measure:** Demilitarization: No Fiig:

A039b0