NSN 5935-00-994-8683

Electrical Receptacle Connector - Page 1 of 2



| Ziotinoai riotopiaolo deliniottei i ago i el Z | |
|---|--|
| View Online at https://aerobasegroup.com/nsn/5935-00-994-8683 | |
| Body Style: | |
| Straight shape, external coupling strain relief | |
| Overall Height: | |
| 2.500 inches | |
| Overall Width: | |
| 2.500 inches | |
| Body Length: | |
| 3.128 inches | |
| Environmental Protection: | |
| Moisture proof and salt water resistant and vibration proof | |
| Unthreaded Mounting Hole Diameter: | |
| 0.173 inches | |
| Center To Center Distance Between Mounting Facilities Parallel To Height: | |
| 1.938 inches | |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: | |
| 1.938 inches | |
| Distance From Mounting Shoulder To Front Face: | |
| 1.021 inches | |
| Mating End Quantity: | |
| 1 | |
| Contact Position Arrangement Style: | |
| 36-10 single mating end | |
| Contact Removability: | |
| Removable single mating end single contact grouping | |
| Polarization Method: | |
| Mating end | |
| Shell Type: | |
| Solid | |
| Connector Locking Method: | |
| Spring friction | |
| Connector Cable Strain Relief Method: | |
| Cable clamp | |
| Terminal Location: | |
| | |

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Rubber single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

NSN 5935-00-994-8683

Electrical Receptacle Connector - Page 2 of 2



| Terminal Type: | | |
|--|--|--|
| Crimp single mating end single contact grouping | | |
| Shell Material: | | |
| Aluminum alloy | | |
| Shell Surface Treatment: | | |
| Cadmium | | |
| Shell Surface Treatment Specification: | | |
| Qq-p-416, type 2, cl 3 federal specification single treatment response | | |
| Included Contact Quantity: | | |
| 48 single mating end single contact grouping | | |
| Included Contact Type: | | |
| Round pin single mating end single contact grouping | | |
| Precious Material And Location: | | |
| Contact surfaces gold | | |
| Precious Material And Weight: | | |
| 0.048 gold grains, troy | | |
| Precious Material: | | |
| Gold | | |
| Shelf Life: | | |
| N/a | | |
| Unit Of Measure: | | |
| | | |
| Demilitarization: | | |
| No | | |
| Fiig: | | |
| A039b0 | | |
| Mil-std (military Standard): | | |
| Mil-g-45204 spec. | | |
| | | |