## NSN 5935-00-995-4398

**Body Style:** 

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-995-4398

Straight shape
Overall Height:
2.219 inches
Overall Diameter:
1.531 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
"3, 5-50, 6-50" single mating end
Contact Removability:
Nonremovable single mating end all contact groupings
Contact Maximum Current Rating In Amps:
15.0 single mating end all contact groupings
Contact Maximum Ac Voltage Rating In Volts:
125.0 single mating end all contact groupings
Contact Maximum Dc Voltage Rating In Volts:
125.0 single mating end all contact groupings
Polarization Method:
Mating end
Shell Type:
Solid
Solid  Connector Locking Method:
Connector Locking Method:
Connector Locking Method: Spring friction
Connector Locking Method: Spring friction Terminal Location:
Connector Locking Method:  Spring friction  Terminal Location:  Back single mating end all contact groupings
Connector Locking Method: Spring friction Terminal Location: Back single mating end all contact groupings Contact Material:
Connector Locking Method: Spring friction Terminal Location: Back single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings
Connector Locking Method: Spring friction Terminal Location: Back single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment:
Connector Locking Method: Spring friction Terminal Location: Back single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment: Gold single mating end all contact groupings
Connector Locking Method: Spring friction Terminal Location: Back single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment: Gold single mating end all contact groupings Insert Material:
Connector Locking Method: Spring friction Terminal Location: Back single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment: Gold single mating end all contact groupings Insert Material: Plastic single mating end
Connector Locking Method: Spring friction Terminal Location: Back single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment: Gold single mating end all contact groupings Insert Material: Plastic single mating end Terminal Type:
Connector Locking Method: Spring friction Terminal Location: Back single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment: Gold single mating end all contact groupings Insert Material: Plastic single mating end Terminal Type: Tab, solder lug single mating end all contact groupings
Connector Locking Method: Spring friction Terminal Location: Back single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment: Gold single mating end all contact groupings Insert Material: Plastic single mating end Terminal Type: Tab, solder lug single mating end all contact groupings Shell Material:
Connector Locking Method: Spring friction Terminal Location: Back single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment: Gold single mating end all contact groupings Insert Material: Plastic single mating end Terminal Type: Tab, solder lug single mating end all contact groupings Shell Material: Metal

0.003 gold grains, troy

**Precious Material And Weight:** 

Contact surfaces gold

## NSN 5935-00-995-4398

Electrical Plug Connector - Page 2 of 2



Gold

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0