Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-996-1005

# Body Length:

1.188 inches

# **Overall Diameter:**

1.375 inches

# **Environmental Protection:**

Moisture proof and salt water resistant and vibration resistant

## Distance From Mounting Shoulder To Front Face:

0.691 inches

#### Mounting Facility Thickness:

0.125 inches

### Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

14-12 single mating end

#### **Contact Removability:**

Removable single mating end all contact groupings

## Contact Maximum Current Rating In Amps:

7.5 single mating end 2nd contact grouping

## **Polarization Method:**

Keyway or multiple keyway

## Insert Position In Deg:

0.0

#### Shell Type:

Solid

### **Connector Locking Method:**

Bayonet shell

### **Terminal Location:**

Back single mating end all contact groupings

### **Contact Surface Treatment:**

Gold single mating end all contact groupings and silver single mating end all contact groupings

### **Terminal Type:**

Crimp single mating end all contact groupings

#### Shell Material:

Aluminum alloy

#### Shell Surface Treatment:

Cadmium

## Included Contact Quantity:

8 single mating end 2nd contact grouping

## Included Contact Type:

Round pin single mating end 2nd contact grouping

# **Precious Material And Location:**

Contact surfaces gold and contact surfaces silver



**Precious Material And Weight:** 

 $0.028 \ \text{gold} \ \text{grains}, \ \text{troy} \ \text{and} \ 0.028 \ \text{silver} \ \text{grains}, \ \text{troy}$ 

# **Precious Material:**

Gold and silver

Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

Fiig:

A039b0