## NSN 5935-00-996-1005

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-996-1005				
Body Length:				
1.188 inches				
Overall Diameter:				
1.375 inches				
Environmental Protection:				
Moisture proof and salt water resistant and vibration resistant				
Distance From Mounting Shoulder To Front Face:				
0.691 inches				
Mounting Facility Thickness:				
0.125 inches				
Mating End Quantity:				
1				
Contact Position Arrangement Style:				
14-12 single mating end				
Contact Removability:				
Removable single mating end all contact groupings				
Contact Maximum Current Rating In Amps:				
7.5 single mating end 2nd contact grouping				
Polarization Method:				
Keyway or multiple keyway				
Insert Position In Deg:				
0.0				
Shell Type:				
Solid				
Connector Locking Method:				
Bayonet shell				
Terminal Location:				
Back single mating end all contact groupings				
Contact Surface Treatment:				
Gold single mating end all contact groupings and silver single mating end all contact groupings				
Terminal Type:				
Crimp single mating end all contact groupings				
Shell Material:				
Aluminum alloy				
Shell Surface Treatment:				
Cadmium				
Included Contact Quantity:				
8 single mating end 2nd contact grouping				
Included Contact Type:				
Pound his single mating and 2nd contact grouping				

Round pin single mating end 2nd contact grouping

**Precious Material And Location:** 

Contact surfaces gold and contact surfaces silver

## NSN 5935-00-996-1005

Electrical Receptacle Connector - Page 2 of 2



Precious	Material	And	Weight:
----------	----------	-----	---------

0.028 gold grains, troy and 0.028 silver grains, troy

**Precious Material:** 

Gold and silver

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0