

View Online at <https://aerobasegroup.com/nsn/5935-00-996-1989>

Body Style:

Straight shape

Overall Length:

Between 1.350 inches and 1.385 inches

Overall Height:

Between 0.995 inches and 1.010 inches

Overall Width:

Between 4.297 inches and 4.325 inches

Environmental Protection:

Corrosion resistant and moisture resistant and thermal shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.197 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.886 inches and 0.895 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 3.870 inches and 3.880 inches

Distance From Mounting Shoulder To Front Face:

Between 0.519 inches and 0.534 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

"78, 078" single mating end

Contact Removability:

Removable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

7.5 single mating end 1st contact grouping

Polarization Method:

Mating end and 2 polarization posts

Shell Type:

Solid

Connector Locking Method:

Friction

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings and copper single mating end all contact groupings

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification all treatment responses single mating end all contact groupings

Terminal Type:

Crimp single mating end all contact groupings

Contact Material Specification:

Qq-c-533 federal specification single material response single mating end all contact groupings

Guide Design And Location:

Hexagon shape male post left-hand top at 6 oclock and hexagon shape male post right-hand bottom at 6 oclock

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Nickel

Included Contact Quantity:

40 single mating end 2nd contact grouping

Included Contact Type:

Round socket single mating end all contact groupings

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.078 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.