

View Online at <https://aerobasegroup.com/nsn/5935-00-996-1989>

**Body Style:**

Straight shape

**Overall Length:**

Between 1.350 inches and 1.385 inches

**Overall Height:**

Between 0.995 inches and 1.010 inches

**Overall Width:**

Between 4.297 inches and 4.325 inches

**Environmental Protection:**

Corrosion resistant and moisture resistant and thermal shock resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:**

0.197 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

Between 0.886 inches and 0.895 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 3.870 inches and 3.880 inches

**Distance From Mounting Shoulder To Front Face:**

Between 0.519 inches and 0.534 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

"78, 078" single mating end

**Contact Removability:**

Removable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:**

7.5 single mating end 1st contact grouping

**Polarization Method:**

Mating end and 2 polarization posts

**Shell Type:**

Solid

**Connector Locking Method:**

Friction

**Terminal Location:**

Back single mating end all contact groupings

**Contact Material:**

Copper alloy single mating end all contact groupings

**Contact Surface Treatment:**

Gold single mating end all contact groupings and copper single mating end all contact groupings

**Insert Material:**

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification all treatment responses single mating end all contact groupings

**Terminal Type:**

Crimp single mating end all contact groupings

**Contact Material Specification:**

Qq-c-533 federal specification single material response single mating end all contact groupings

**Guide Design And Location:**

Hexagon shape male post left-hand top at 6 oclock and hexagon shape male post right-hand bottom at 6 oclock

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Nickel

**Included Contact Quantity:**

40 single mating end 2nd contact grouping

**Included Contact Type:**

Round socket single mating end all contact groupings

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.078 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.