Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-998-1797

Body Style:
Straight shape
Overall Length:
1.870 inches
Overall Height:
0.840 inches
Overall Width:
0.620 inches
Unthreaded Mounting Hole Diameter:
0.150 inches
Distance Between Mounting Facility Centers:
1.500 inches
Mating End Quantity:
1
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
15.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
125.0 single mating end single contact grouping
Polarization Method:
Contact
Shell Type:
Shell Type: Solid
Solid
Solid Connector Locking Method:
Solid Connector Locking Method: Friction
Solid Connector Locking Method: Friction Terminal Location:
Solid Connector Locking Method: Friction Terminal Location: Back single mating end single contact grouping
Solid Connector Locking Method: Friction Terminal Location: Back single mating end single contact grouping Contact Material:
Solid Connector Locking Method: Friction Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping
Solid Connector Locking Method: Friction Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment:
Solid Connector Locking Method: Friction Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Cadmium single mating end single contact grouping
Solid Connector Locking Method: Friction Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Cadmium single mating end single contact grouping Insert Material:
Solid Connector Locking Method: Friction Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Cadmium single mating end single contact grouping Insert Material: Plastic phenolic single mating end
Solid Connector Locking Method: Friction Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Cadmium single mating end single contact grouping Insert Material: Plastic phenolic single mating end
Solid Connector Locking Method: Friction Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Cadmium single mating end single contact grouping Insert Material: Plastic phenolic single mating end Terminal Type: Tab, solder lug single mating end single contact grouping
Solid Connector Locking Method: Friction Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Cadmium single mating end single contact grouping Insert Material: Plastic phenolic single mating end Terminal Type: Tab, solder lug single mating end single contact grouping Shell Material:
Solid Connector Locking Method: Friction Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Cadmium single mating end single contact grouping Insert Material: Plastic phenolic single mating end Steel
Solid Connector Locking Method: Friction Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Cadmium single mating end single contact grouping Insert Material: Plastic phenolic single mating end Single Contact grouping Terminal Type: Tab, solder lug single mating end single contact grouping Shell Material: Steel Shell Surface Treatment:
Solid Connector Locking Method: Friction Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Cadmium single mating end single contact grouping Insert Material: Plastic phenolic single mating end Steel Shell Material: Steel Shell Surface Treatment: Cadmium



Included Contact Type:

Round pin single mating end single contact grouping

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0