

View Online at <https://aerobasegroup.com/nsn/5935-00-998-7802>

**Body Style:**

Straight shape, external coupling

**Overall Length:**

1.080 inches

**Overall Height:**

Between 1.027 inches and 1.037 inches

**Overall Width:**

Between 1.027 inches and 1.037 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.120 inches and 0.130 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

Between 0.807 inches and 0.817 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 0.807 inches and 0.817 inches

**Distance From Mounting Shoulder To Front Face:**

0.562 inches

**Mating End Quantity:**

1

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

7.5 single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet latch

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Aluminum

**Shell Surface Treatment:**

Anodize

**Shell Surface Treatment Specification:**

Mil-a--8625, type 1 military specification single treatment response

**Insert Material Specification:**

Mil-m-14 military specification single material response single mating end

**Included Contact Quantity:**

5 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Special Features:**

Furnished items - grommet

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-m-14 spec.