

View Online at <https://aerobasegroup.com/nsn/5935-00-999-4723>

Body Style:

Straight edge type

Overall Length:

4.285 inches

Overall Height:

0.692 inches

Overall Width:

0.340 inches

Environmental Protection:

Salt water resistant and vibration resistant and moisture resistant

Unthreaded Mounting Hole Diameter:

0.142 inches

Distance Between Mounting Facility Centers:

4.031 inches

Board Accommodated Length:

3.596 inches single board

Board Accommodated Width:

0.062 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of independent contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

830.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

1270.0 single mating end single contact grouping

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Tab, solder lug single mating end single contact grouping

Insert Material Specification:

Mil-m-14, type sgd-f military specification single material response single mating end

Included Contact Quantity:

44 single mating end single contact grouping

Included Contact Type:

Bifurcated spring single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.044 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.