

View Online at <https://aerobasegroup.com/nsn/5935-00-999-5167>

Thread Class:

2a and 2b and 2a

Thread Direction:

Right-hand

Body Style:

Straight shape

Overall Length:

0.780 inches

Overall Height:

0.530 inches

Overall Width:

0.230 inches

Environmental Protection:

Pressure proof and moisture resistant and salt water resistant and vibration resistant

Distance Between Mounting Facility Centers:

0.531 inches

Threaded Device Type:

Coupling facility and mounting stud

Mating End Quantity:

1

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

Polarization Method:

Jackscrew

Connector Locking Method:

Jackscrew-socket

Thread Length:

0.130 inches and 0.110 inches and 0.196 inches

Thready Qty Per Inch (tpi):

56

Thread Size:

0.086 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Included Contact Quantity:

5 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.005 gold grains, troy and 0.005 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0