NSN 5935-00-999-7054



Connector Adapter - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-00-999-7054 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape w/flange **Overall Length:** 2.125 inches **Overall Height:** 2.500 inches **Overall Width:** 2.500 inches **Environmental Protection:** Moisture proof and salt water resistant and vibration proof **Unthreaded Mounting Hole Diameter:** 0.173 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 1.938 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.938 inches **Distance From Mounting Shoulder To Front Face:** 0.985 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 36-10 all mating ends **Contact Removability:** Nonremovable all mating ends single contact grouping **Contact Maximum Current Rating In Amps:** 22.0 all mating ends single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 all mating ends single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 all mating ends single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 125.0

Shell Type:

Solid

NSN 5935-00-999-7054

Connector Adapter - Page 2 of 2



Connector Locking Method:
Externally threaded shell
Thread Length:
0.630 inches
Thready Qty Per Inch (tpi):
16
Thread Size:
2.500 inches
Contact Material:
Copper alloy all mating ends single contact grouping
Contact Surface Treatment:
Silver all mating ends single contact grouping
Insert Material:
Rubber all mating ends
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification all treatment responses
Insert Material Specification:
Mil-r-3065 military specification single material response all mating ends
Included Contact Quantity:
48 all mating ends single contact grouping
Included Contact Type:
Round socket 2nd mating end single contact grouping
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.096 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Un
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):

Mil-r-3065 spec.