

View Online at <https://aerobasegroup.com/nsn/5935-01-003-0422>

**Body Style:**

Straight shape

**Overall Length:**

2.635 inches

**Overall Height:**

0.683 inches

**Overall Width:**

0.605 inches

**Environmental Protection:**

Moisture resistant and vibration resistant and shock resistant and corrosion resistant

**Unthreaded Mounting Hole Diameter:**

0.120 inches

**Distance Between Mounting Facility Centers:**

2.406 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

43w2 single mating end

**Contact Removability:**

Nonremovable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:**

5.0 single mating end all contact groupings

**Polarization Method:**

Mating end

**Shell Type:**

Solid

**Connector Locking Method:**

Friction

**Terminal Location:**

Back single mating end all contact groupings

**Contact Material:**

Copper alloy single mating end all contact groupings

**Contact Surface Treatment:**

Gold single mating end all contact groupings

**Insert Material:**

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end all contact groupings

**Terminal Type:**

Solder well single mating end all contact groupings

**Shell Material:**

Steel

**Shell Surface Treatment:**

Cadmium

**Insert Material Specification:**

Mil-p-19833, ty gdi-30f military specification single material response single mating end

**Included Contact Quantity:**

41 single mating end 2nd contact grouping

**Included Contact Type:**

Round socket single mating end all contact groupings

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.043 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.