

View Online at <https://aerobasegroup.com/nsn/5935-01-004-1539>

Environmental Protection:

Vibration resistant and shock resistant and corrosion resistant and moisture resistant and pressure proof

Mating End Quantity:

1

Contact Position Arrangement Style:

Bsm single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Frequency Rating:

500.0 megahertz single mating end single contact grouping

Polarization Method:

Key, multiple key groove

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Silver single mating end single contact grouping and gold single mating end single contact grouping

Insert Material:

Plastic polytetrafluoroethylene single mating end

Contact Surface Treatment Specification:

Mil-f-14072, type ii, grade a military specification 1st treatment response single mating end single contact grouping and mil-g-45204, type i, class 1 military specification 2nd treatment response single mating end single contact grouping

Contact Material Specification:

Qq-c-530, condition h, heat treat to condition ht federal specification single material response single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Silver

Shell Surface Treatment Specification:

Mil-f-14072, type ii, grade a military specification single treatment response

Shell Material Specification:

Qq-b-626, composition 22, half hard federal specification single material response

Insert Material Specification:

Mil-p-19468 military specification single material response single mating end

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material:

Silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-f-14072 spec.