Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-004-3446

# Thread Class:

2a

**Thread Direction:** 

Right-hand

# **Body Style:**

Straight shape, external coupling

# **Overall Length:**

1.191 inches

**Overall Height:** 

1.281 inches

**Overall Width:** 

1.281 inches

### **Environmental Protection:**

Corrosion resistant and moisture resistant and vibration resistant

### **Unthreaded Mounting Hole Diameter:**

### Between 0.115 inches and 0.130 inches

# Center To Center Distance Between Mounting Facilities Parallel To Height:

0.969 inches

# Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.969 inches

# Distance From Mounting Shoulder To Front Face:

Between 0.562 inches and 0.593 inches

#### **Threaded Device Type:**

Coupling facility

# Mating End Quantity:

1

# **Contact Position Arrangement Style:**

16s-8 single mating end

# **Contact Removability:**

Nonremovable single mating end single contact grouping

# **Contact Maximum Current Rating In Amps:**

22.0 single mating end single contact grouping

# Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

# Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end single contact grouping

## **Polarization Method:**

Keyway or multiple keyway

# **Insert Position In Deg:**

0.0

### Shell Type:

Solid



### **Connector Locking Method:**

Externally threaded shell

## **Thread Length:**

0.375 inches

# Thread Size:

1.000 inches

## **Terminal Location:**

Back single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping or silver single mating end single contact

#### grouping

# **Terminal Type:**

Solder well single mating end single contact grouping

### Shell Material:

Aluminum alloy

# Shell Surface Treatment:

Cadmium

# Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

# **Included Contact Quantity:**

5 single mating end single contact grouping

#### Included Contact Type:

Round socket single mating end single contact grouping

# **Precious Material And Location:**

Contact surface gold and contact surface silver

#### **Precious Material:**

Gold and silver

# **Test Data Document:**

81349-milc5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Thread Series Designator:**

Unef

Shelf Life:

N/a

### Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0