# NSN 5935-01-004-3449

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-004-3449 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 0.875 inches **Overall Height:** 0.484 inches **Overall Width:** 0.203 inches **Distance Between Mounting Facility Centers:** 0.656 inches **Threaded Device Type:** Mounting stud **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 9 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Jackscrew **Connector Locking Method:** Jackscrew-socket Thread Length: 0.219 inches Thready Qty Per Inch (tpi): 56 **Thread Size:** 0.086 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and copper single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Solder well single mating end single contact grouping

# NSN 5935-01-004-3449

Electrical Receptacle Connector - Page 2 of 2



#### **Contact Material Specification:**

Qq-b-750 comp a federal specification single material response single mating end single contact grouping

## **Insert Material Specification:**

Mil-m-19833, type gdi-30f military specification single material response single mating end

## **Included Contact Quantity:**

9 single mating end single contact grouping

## **Included Contact Type:**

Round socket single mating end single contact grouping

#### **Precious Material And Location:**

Contact surface gold

Precious Material:

Gold

**Thread Series Designator:** 

Unc

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-19833 spec.