Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-004-7997

Body Style:

Right angle, card

Overall Length:

Between 1.195 inches and 1.205 inches

Overall Width:

Between 0.345 inches and 0.355 inches

Body Height:

Between 0.340 inches and 0.350 inches

Environmental Protection:

Shock resistant and vibration resistant and corrosion resistant and humidity resistant

Mating End Quantity:

1

Contact Position Arrangement Style:

3 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Connector Locking Method:

Friction

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy 510 single mating end single contact grouping or copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate glass filled single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type ii, class 1, grade c military specification 1st treatment response single mating end single contact grouping and mil-c-14550

military specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Contact Material Specification:

Qq-w-401 federal specification 1st material response single mating end single contact grouping or qq-b-626 federal specification 2nd material response single mating end single contact grouping or qq-w-321 federal specification 2nd material response single mating end single contact grouping or qq-c-530 federal specification 2nd material response single mating end single contact grouping or qq-c-530 federal specification 2nd material response single mating end single contact grouping or qq-c-530 federal specification 2nd material response single mating end single contact grouping or qq-c-530 federal specification 2nd material response single mating end single contact grouping

Insert Material Specification:

aludad Cantaat Quantity

Mil-m-14, type sdg-f military specification single material response single mating end or mil-p-19833, type gdi-30f military specification single material response single mating end

Unable To Decode:

Unable to decode and unable to decode



Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.025 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.