

View Online at <https://aerobasegroup.com/nsn/5935-01-004-7998>

Body Style:

Right angle, card

Overall Length:

1.150 inches

Overall Width:

Between 0.243 inches and 0.257 inches

Body Height:

Between 0.253 inches and 0.267 inches

Environmental Protection:

Vibration resistant and shock resistant and salt water resistant and humidity resistant

Mating End Quantity:

1

Contact Position Arrangement Style:

17 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Beryllium single mating end single contact grouping and copper single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-c-14550 military specification 1st treatment response single mating end single contact grouping and mil-g-45204, type ii, class i, grade c military specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Contact Material Specification:

Qq-w-401 federal specification 1st material response single mating end single contact grouping or qq-b-626 federal specification 2nd material response single mating end single contact grouping or qq-w-321 federal specification 3rd material response single mating end single contact grouping or qq-s-763 federal specification 4th material response single mating end single contact grouping

Included Contact Quantity:

17 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-c-14550 spec.