

View Online at https://aerobasegroup.com/nsn/5935-01-004-9306

Thread Class:
2a and 2a
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape, external coupling Overall Length:
1.430 inches
Overall Height:
Between 1.120 inches and 1.130 inches
Overall Width:
Between 1.120 inches and 1.130 inches
Environmental Protection:
Humidity resistant and pressure proof and shock proof and vibration resistant
Unthreaded Mounting Hole Diameter:
Between 0.116 inches and 0.125 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 0.901 inches and 0.911 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 0.901 inches and 0.911 inches
Distance From Mounting Shoulder To Front Face:
Between 0.708 inches and 0.728 inches
Threaded Device Type:
Back shell and coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
14-7 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Thread Length:
0.290 inches and 0.218 inches
Thready Qty Per Inch (tpi):
20 and 20

NSN 5935-01-004-9306

Electrical Receptacle Connector - Page 2 of 2



Thread Size:
0.875 inches and 0.938 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Material Specification:
Qq-a-367 federal specification single material response
Included Contact Quantity:
7 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.007 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-83723 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef and unef
Specification Data:
81349-mil-c-83723/83 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Filg:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.